

MPC[®]KIT

MULTI-PURPOSE COMBO KIT

SCHONSTEDT 
INSTRUMENT COMPANY
Making Locating Easier Since 1953

**NEW FOR
2012**

REPLACES MAC-51BX



The most
portable,
versatile, and
accurate way to
**Find it All
Underground**

Magnetic Locator



Pipe & Cable Locator



CABLE TV LINES • CAST OR DUCTILE IRON PIPES

COPPER PIPE • CORNER MARKERS • CURB & VALVE BOXES

ENCLOSURES • FIBER OPTIC W/ TRACER OR SHIELD

GAS LINES • WEAPONS • HAZMAT DRUMS • IRRIGATION LINES

MAG & PK NAILS • MANHOLE COVERS • MARKER MAGNETS

MUNITIONS • PLASTIC PIPE W/ TRACER WIRE • POWER LINES

SEPTIC TANKS • STEEL PIPES • STREET LIGHT POWER

TELEPHONE LINES • WATER & SEWER LINES • WELL CASINGS

MPCKIT includes

- **GA-92XTd Magnetic Locator**
- **XTpc Pipe & Cable Locator**
- Inductive Antenna • Transmitter • Holster Clip • Ground Stake
- Power Supply & Charger for XTpc (AC/DC)
- Conductive Clips Assembly • Small Heavy Duty Conductive Clip
- Locating 101 Manual • Instruction Manual for XTpc & GA-92XTd
- Rugged carrying hard case with custom foam insert

Available in 3 models:

MPC-800: Includes an XTpc-82 Pipe & Cable Locator and a GA-92XTd Magnetic Locator

MPC-300: Includes an XTpc-33 Pipe & Cable Locator and a GA-92XTd Magnetic Locator

MPC-500: Includes an XT-512 Camera & Sonde Locator and a GA-92XTd Magnetic Locator



GA-92XTd Specifications

Output	<p>Audio: Signal increases in frequency with gradient field intensity. Idle frequency = 10 Hz.</p> <p>Visual: Expanding bar-graphs indicate polarity (positive or negative) and relative signal strength</p>
Battery Indicator	4-segment LCD
Gain	Continuous control
Volume	Continuous control
Input Power	Supplied by one 9 V battery (Lithium recommended, but not required)
Battery Life	24 Hours (intermittent usage)
Operating Temperature	-13° F to 140° F (25° C to 60° C)
Water Resistant Length	11.5 in (~29 cm) (when extended)
Overall Length	<p>Unit extended: 26 in (~66 cm)</p> <p>Unit collapsed: 15.5 in (~39 cm)</p>
Weight	Approximately 2.4 Lbs (1.1 Kg)

XTpc Receiver Specifications

Operating Frequency	82kHz or 33kHz plus 50/60Hz passive detection (factory selectable)
Battery	9 V single battery
Battery Life	18 hrs intermittent use
LCD Display	3 1/2 digit reflective Signal Strength, Directional Arrows, Battery Status, Volume and Depth
Controls	ON/Volume adjustment, OFF, DEPTH, SONDE, AUTO GAIN, UP gain, DOWN gain, PASSIVE
Dimensions	Unit extended: 26 in (~66 cm) Unit collapsed: 15.5 in (~39 cm)
Weight	Under 2.5 Lbs

XTpc Transmitter Specifications

Operating Frequency	82kHz or 33kHz (factory selectable)
Dimensions	7.2" L x 2.2" W x 1.5" H
Battery Type	Rechargeable NiMH 7.2 V, 3800mAh
Battery Life	8 hours continuous use
Output Power	Maximum 1-watt allowed under FCC at 82kHz; 1.8-watt at 33kHz
Controls	ON/OFF UP Power DOWN Power
LCD	3 1/2 digit reflective Battery Status, Mode, Output Power Level, Output Current (mA)
Weight	Under 2 lbs

Order/Info Hotline:
800-999-8280

Order/Info Online:
www.schonstedt.com



SCHONSTEDT 
INSTRUMENT COMPANY

Making Locating Easier Since 1953
an employee-owned company